

MATERIAL SAFETY DATA SHEET

ChemCo Systems, Inc., 2800 Bay Rd., Redwood City, CA 94063

Prepared by Dept. of Safety, Phone: 650.261.3790

24 Hour Emergency Phone: 800.424.9300 (202-483-7616) CHEMTREC

1. PRODUCT NAME:

CCS™ Grout, Control Joint - HB, Part B

Chemical Family: Amino compounds, diluent, fillers.

2. HAZARDOUS INGREDIENTS

NAME	CAS No.	TLV	STEL	PEL	CONTENT
Nonyl Phenol	25154-52-3	none	none	none	72-78%
Amino ethyl piperazine (AEP)	140-31-8	none	none	none	20-30%
Diethylenetriamine	111-40-0	1ppm	none	1ppm	1-2%

reference section 7, Health Hazard Data for LD (50)

3. PHYSICAL DATA:

Boiling Point:	316 C (DNP)	Water/Oil Distribution Coefficient:	N/D
Percent Volatile:	negligible	Solubility in Water:	30%
Freezing Point	N/D	Specific Gravity:	0.95
Vapor Pressure@ 20C:	N/D	pH:	alkaline
Vapor Density	Heavier than air	Evaporation Rate:	N/D
Odor Threshold	N/D	Odor	Ammoniacal
Appearance	Straw-clear liquid		

N/D = Not Determined

4. FIRE AND EXPLOSION HAZARD DATA:

HMIS Health Rating: 1 - (Slight Hazard)

Flash Point: 99 C (210 F) (AEP) PMCC
Auto Ignition Temperature: N/D
Limits of Flammability: LEL: 1.8% @ 140 C UEL: N/D

EXTINGUISHING MEDIA:

CARBON DIOXIDE, FOAM, DRY CHEMICAL & WATER FOG.
SPECIAL FIRE & UNUSUAL HAZARDS: Self-contained respirator equipment and full protective clothing are required when smoke and fumes are generated. Electrical grounding is not recommended.

5. REACTIVITY DATA:

HMIS Reactivity Rating: 1 - (Slight Hazard)

STABILITY: Stable. This product must be mixed with another component to react. Not sensitive to mechanical impact.

INCOMPATIBILITY: Strong oxidizing agents, acids, isocyanates and organic peroxides may result in violent explosive reactions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and dioxide, nitrogen oxides and various hydrocarbons from incomplete combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

6. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS AND LEAKS: Ventilate area. Wear appropriate protective gear. Contain leak/spill. Clean up residue with absorbent material. Wash down area with water and diluted acetic acid.

WASTE DISPOSAL METHOD: Handle disposal of waste material in manner which complies with local, state, province, and federal regulations. Landfill if solidified or incinerate at agency approved waste-disposal facility.

7. HEALTH HAZARD DATA:

HMIS Health Rating: 2 - (Moderate Hazard)

Primary Route Of Entry: Dermal, eyes ingestion.

Effects of Overexposure:

Inhalation:	Low degree of volatility. At higher temperatures, it is possible for vapors to be generated. Vapors are very disagreeable. This material may result in irritation of throat and lungs and an allergic type reaction in some individuals.
Eyes:	Contact can cause severe burn. At higher temperature vapors can cause severe irritation, redness, tearing or blurred vision.
Skin Contact:	Short single exposure may cause moderate irritation to mild burn. Prolonged or repeated exposure may cause a severe burn. May result in an allergic reaction or sensitization response in some individuals.
Skin Absorption:	Amine may be absorbed through the skin in moderately toxic amounts. LD(50) CAS 140-31-8 (AEP) 880mg/kg (Rabbit) LD (50) CAS 111-40-0 (DETA) 880mg/kg (Rabbit)
Ingestion:	Intake can cause gastrointestinal irritation, nausea, vomiting, diarrhea, headache and drowsiness. Can result in burns of mouth esophagus and stomach. LD (50) CAS 140-31-8 (AEP) 2140 mg/kg (Rat)
Chronic:	None known.

8: FIRST AID:

Eyes:	Flush eyes with water and/or 1% boric acid, lifting upper and lower lids occasionally for 30 minutes. Seek prompt medical attention.
Skin:	Wash with soap and water for at least 15 minutes. Remove contaminated clothing and wash before re-use. Destroy contaminated leather. Seek medical attention if irritation persists.
Ingestion:	Do not induce vomiting. Give large quantities of water or diluted water with acetic acid. Get immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person.
Inhalation:	Remove victim from exposure. If difficulty with breathing; administer oxygen and seek immediate medical assistance.

9. SPECIAL PROTECTION INFORMATION:

HMIS Personal Protection Rating: C (Safety Glasses, Gloves, Apron)

Ventilation	Ventilation at normal room temperature is a means of controlling vapor properly. If material is above 140 F, a positive pressure breathing apparatus is recommended.
Personal Protection:	Use eye protection and gloves. Selection of specific items such as gloves, boots and apron will depend on the operation. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard. Confined spaces, rooms or tanks are areas where concern for TLV's is especially important. Reference OSHA Regulation CFR 29 1910.134 for recommended respiratory protection.

10. ADDITIONAL INFORMATION:

DOT Proper Shipping Name:	N-aminoethyl piperazine mixture
DOT Hazard Class or Division:	8
Identification Number:	UN 2815
Packing group:	III
Labels Required:	CORROSIVE
WHMIS Classification:	Class D, Div. II, Sub. A, Class E.
WHMIS Labeling:	Test tube, hand.
Storage Conditions:	Keep containers tightly sealed; store in cool and dry area. Avoid freezing conditions.
Shelf life:	Indefinite
Special Instructions:	None.