

# MATERIAL SAFETY DATA SHEET

ChemCo Systems, Inc., 2800 Bay Road, Redwood City, CA 94063-3503  
Prepared by Dept. of Safety, Phone: 650/261-3790

24 Hour Emergency Phone: 800.424.9300 (202-483-7616) CHEMTREC

## PRODUCT NAME:

**CCS™ Coating, Epoxy Healer/Sealer, Part A**  
Chemical Family: Epoxy resin, diluents.

## 2. HAZARDOUS INGREDIENTS

NAME	CAS No.	TLV	STEL	PEL	CONTENT
Epoxy resin	25068-38-6	none	none	none	50-60%
Epoxy resin (CGE)	2210-79-9	none	none	none	15-25%
Hexanedioldiacrylate	13048-33-4	none	none	none	10-20%
Trimethylolpropanetri-acrylate	15625-89-5	none	none	none	5-10%

reference section 7, Health Hazard Data for LD (50)

## 3. PHYSICAL DATA:

Boiling Point:	>125 C	Water/Oil Distribution Coefficient:	N/D
Percent Volatile:	Negligible	Solubility in Water:	Minimal
Freezing Point	N/D	Specific Gravity:	1.12
Vapor Pressure @ 20C:	N/D	pH:	N/D
Vapor Density	N/D	Evaporation Rate:	N/D
Odor Threshold	N/D	Odor	Slight
Appearance	Amber liquid		

N/D = Not Determined

## 4. FIRE AND EXPLOSION HAZARD DATA:

**HMIS Flammability Rating: 1 - (Slight Hazard)**

Flash Point: >94 C (PMCC)  
Auto Ignition Temperature: N/D  
Limits of Flammability: LEL: N/D UEL: N/D

### EXTINGUISHING MEDIA:

CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.

**SPECIAL FIRE & UNUSUAL HAZARDS:** At high temperatures vapors can cause pressure build-up in sealed containers. Use water to cool containers exposed to fire. Self-contained respirator equipment and full protective clothing are required when smoke and fumes are generated. Electrical grounding is not recommended.

## 5. REACTIVITY DATA:

**HMIS Reactivity Rating: 2 - (Moderate Hazard)**

**STABILITY:** This product may spontaneously polymerize generating heat, if exposed to high temperatures or upon inhibitor depletion. Not sensitive to mechanical impact. Closed containers may rupture or explode during runaway polymerization.

**INCOMPATIBILITY:** Strong acids, strong bases. Peroxides, amines and mercaptans may initiate possible hazardous polymerization.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and dioxide, aldehydes, various hydrocarbons from incomplete combustion.

**HAZARDOUS POLYMERIZATION:** May occur if product is not handled per instructions.

## 6. ENVIRONMENTAL AND DISPOSAL INFORMATION:

**ACTION TO TAKE FOR SPILLS AND LEAKS:** Ventilate area. Eliminate all sources of ignition. Wear appropriate protective gear. Contain leak/spill. Salvage. Clean up residue with absorbent material.

**WASTE DISPOSAL METHOD:** Handle disposal of waste material in manner which complies with local, state, province, and federal regulations. Landfill if solidified or incinerate at agency approved waste-disposal facility.

## 7. HEALTH HAZARD DATA:

**HMIS Health Rating: 2 - (Moderate Hazard)**

Primary Route Of Entry: Dermal

### Effects of Overexposure:

Skin Contact:	Prolonged or repeated exposure may cause skin irritation and redness. Skin sensitization or allergic reaction may occur in some individuals.
Skin absorption	Prolonged or repeated exposure can result in significant absorption.
Eyes:	Contact may cause irritation, redness, tearing and blurred vision.
Inhalation:	Vapors may cause severe irritation to nose and mucous membranes.
Ingestion:	Intake can cause gastro-intestinal irritation, nausea, vomiting or diarrhea. LD(50) 25068-38-6 11.4 g/kg (rat); LD(50) 2210-79-9 11.4 g/kg (rat).
Chronic:	None known.

## 8: FIRST AID:

Inhalation:	Remove victim from exposure. If difficulty with breathing; administer oxygen and seek immediate medical assistance.
Eyes:	Flush with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
Skin:	Remove contaminated clothing. Wash with soap and water; get medical attention if irritation persists.
Ingestion:	Do not induce vomiting. Give at least two glasses of water. Get immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Do not give anything by mouth to an unconscious person.

## 9. SPECIAL PROTECTION INFORMATION:

**HMIS Personal Protection Rating: C (Safety Glasses, Gloves, Apron)**

Ventilation:	Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build-up of heavy vapors.
Personal Protection:	Use chemical goggles. Selection of specific items such as gloves, boots and apron will depend on the operation. Wear rubber boots when spreading material on floors. Wear respirator protection at elevated temperatures, when mist conditions persist, whenever airborne concentrations exceed TLV ceilings or TWA. Use NIOSH approved respirators for listed hazard. confined spaces, rooms or tanks or areas where concern for TLV's is especially important. Reference OSHA Regulation CFR 29 1910.134 for recommended respiratory protection.

## 10. ADDITIONAL INFORMATION:

DOT Proper Shipping Name:	Epoxy resin mixture
DOT Hazard Class or Division:	Not regulated
Identification Number:	N/A
Packing Group:	N/A
Labels Required:	N/A
WHMIS Classification:	Class D, Division 2, Sub. B.
WHMIS Labeling	Stylized T
Calif. Prop. 65	This product contains or may contain trace quantities of substances known to the State of California to cause cancer or reproductive toxicity
Storage Conditions:	Keep containers tightly sealed. Store in dry and cool areas.
Shelf life:	9 months in unopened container when stored above 40 and below 90 F and away from sunlight.
Special Instructions:	Keep containers tightly sealed. Store in cool and dry area. Avoid freezing conditions.