MATERIAL SAFETY DATA SHEET

ChemCo Systems, Inc., 2800 Bay Road, Redwood City, CA 94063 Prepared by Dept. of Safety, Phone: 650/261-3790

24 Hour Emergency Phone: 800.424.9300 (202-483-7616) CHEMTREC

1. PRODUCT NAME:

KEMKO® 022, SuperSEAL, Part A

Chemical Family: Epoxy resin, fillers, paste.

2. HAZARDOUS INGREDIENTS

NAME	CAS No.	TLV	STEL	PEL	CONTENT
Epoxy resin	25068-38-6	none	none	none	45-55%
Cresyl glycidyl ether	2210-79-9	none	none	none	2-8%

reference section 7, Health Hazard Data for LD (50)

3. PHYSICAL DATA:

Boiling Point:	>200 C	Water/Oil Distribution Coefficient:	N/D
Percent Volatile:	Slight	Solubility in Water:	Slight
Freezing Point	N/D	Specific Gravity:	1.14
Vapor Pressure@ 20C:	N/D	pH:	N/D
Vapor Density	Heavier than air	Evaporation Rate:	N/D
Odor Threshold	N/D	Odor	Slight
Appearance	White paste		

N/D = Not Determined

4. FIRE AND EXPLOSION HAZARD DATA:

HMIS Flammability Rating:	1 - (Slight Hazard)		
Flash Point:	>92 C (200 F) PMCC		
Auto Ignition Temperature:	N/D		
Limits of Flammability:	LEL: N/D UEL: N/[)	
EXTINGUISHING MEDIA: CARBON DIOXIDE, FOAM, DRY			
SPECIAL FIRE & UNUSUAL HAZARDS: At higher temperature vapors can cause pressure build-up in sealed containers. Use water to cool containers exposed to fire. Self-contained respirator equipment and full protective clothing required when smoke or fumes are generated. Electrical grounding not recommended.			

5. REACTIVITY DATA:			
HMIS Reactivity Rating: 1 - (Slight Hazard)			
STABILITY: This product requires another component to react			
at room temperature. Mix and use product in accordance with			
directions for safety. Excessive heat and fume generation can occur if improperly handled. Not sensitive to mechanical impact.			
INCOMPATIBILITY: Strong acids, strong bases. Amines and mercaptains may initiate possible hazardous polymerization.			
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and dioxide, aldehydes, various compounds from incomplete combustion.			
HAZARDOUS POLYMERIZATION: May occur is product is not handled per instructions.			

6. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS AND LEAKS: Ventilate area, eliminate all sources of ignition. Wear appropriate protective gear. Contain leak/spill. Salvage. Clean up residue with absorbent material. WASTE DISPOSAL METHOD: Handle disposal of waste material in manner which complies with local, state, province, and federal regulations. Landfill if solidified or incinerate at agency approved waste-disposal facility.

7. HEALTH HAZARD DATA:

	/. !!EAE!!!!AE/	AND DATA.
HMIS H	ealth Rating:	2 - (Moderate Hazard)
Primary F	Route Of Entry:	Dermal
	Effects of Overex	cposure:
Skin Contact:		exposure may cause skin Skin sensitization or allergic me individuals.
Eyes:	Contact may cause irr blurred vision.	itation, redness, tearing and
Inhalation:	Vapors may cause se mucous membranes.	evere irritation to nose, and
Ingestion:	Intake can cause gastr vomiting and diarrhea. LD (50) CAS 25068-38-6 LD (50) CAS 2210-79-9	
Chronic:	None known.	

8: FIRST AID:

Inhalation:	Remove victim from exposure. If difficulty with breathing; administer oxygen and seek immediate medical assistance.	
Eyes:	Flush with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.	
Skin:	Wash with soap and water; get medical attention if irritation persists.	
Ingestion:	Do not induce vomiting, give at least two glasses of water; get immediate medical attention. If vomiting occur spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Do not give anything by mouth to an unconscious person.	

9. SPECIAL PROTECTION INFORMATION:

HMIS Persona	al Protection Rating: C (Safety Glasses, Gloves, Apron)
Ventilation:	Ventilation is recommended. Air movement must be
	designed to insure turnover at all locations in work
	area to prevent build-up of heavy vapors.
Personal	Use eye protection. Selection of specific items such as
Protection:	gloves, boots and apron will depend on the operation.

10. ADDITIONAL INFORMATION:

DOT Proper Shipping N	ame: Resin solution, not regulated
DOT Hazard Class or D	ivision: Not regulated
Identification Number:	N/A
Packing Group:	N/A
Labels Required:	N/A
California Prop. 65:	N/A
WHMIS Classification:	Class D, Div. II, Sub. B
WHMIS Labeling:	Stylized T
Storage Conditions:	Keep containers tightly sealed. Store in dry
	and cool areas. Avoid freezing conditions.
Shelf life:	Indefinite.
Special Instructions:	Storage recommendations: Store at room
	temperature. Do not allow to freeze.

The information given herein is given in good faith. No warranty, expressed or implied, is made regarding the accuracy of these data or the results obtained from the use thereof. All materials may present unknown health hazards and must be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Consult ChemCo Systems Inc. for further information.

MSDS022A 04/14