MATERIAL SAFETY DATA SHEET

ChemCo Systems, Inc., 2800 Bay Road, Redwood City, CA 94063 Prepared by Dept. of Safety, Phone: 650/261-3790

24 Hour Emergency Phone: 800.424.9300 (202-483-7616) CHEMTREC

1. PRODUCT NAME:

KEMKO 026, UW IR, Part A

Chemical Family: Epoxy resin, filler mixture.

2. HAZARDOUS INGREDIENTS

				_	
NAME	CAS No.	TLV	STEL	PEL	CONTENT
Epoxy resin	25068-38-6	none	none	none	55-65%
Epoxy resin	17557-23-2	none	none	none	30-40%

reference section 7, Health Hazard Data for LD (50)

3. PHYSICAL DATA:

Boiling Point:	>100 C	Water/Oil Distribution Coefficient:	N/D
Percent Volatile:	Negligible	Solubility in Water:	Minimal
Freezing Point	N/D	Specific Gravity:	1.1
Vapor Pressure @ 20C	N/D	pH:	N/D
Vapor Density	Heavier than air	Evaporation Rate:	N/D
Odor Threshold	N/D	Odor	Mild
Appearance	Amber liquid		

N/D = Not Determined

4. FIRE AND EXPLOSION HAZARD DATA:

HMIS Flammability Rating:		1 - (Slight Hazard)		
	Flash Point:	> 250 F (PMCC)		
	Auto Ignition Temperature:	uto Ignition Temperature: N/D		
	Limits of Flammability:	LEL: N/D	UEL: N/D	
	EXTINGUISHING MEDIA: CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG			
	SPECIAL FIRE & UNUSUAL HAZARDS: Self-contained respirator equipment and full protective clothing required when smoke or fumes			

are generated. Electrical grounding not recommended.

5. REACTIVITY DATA:

5. NEACHVILL DATA.				
HMIS Reactivity Rating: 1 - (Slight Hazard)				
STABILITY: This product must be mixed with another				
component to react at room temperature. Excessive heat and				
fume generation can occur if improperly handled. Not sensitive to mechanical impact.				
INCOMPATIBILITY: Strong acids, strong bases. Amines and mercaptains may initiate possible hazardous polymerization.				
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and dioxide, aldehydes, various hydrocarbons from incomplete combustion.				
HAZARDOUS POLYMERIZATION: May occur is product is no handled per instructions.				

6. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS AND LEAKS: Wear appropriate protective gear. Contain leak/spill. Salvage. Clean up residue with absorbent material.

WASTE DISPOSAL METHOD: Handle disposal of waste material in manner which complies with local, state, province, and federal regulations. Landfill if solidified or incinerate at agency approved waste-disposal facility.

7. HEALTH HAZARD DATA:

HMIS Health Rating:		2 - (Moderate Hazard)	
Primai	ry Route Of Entry:	Dermal	
	Effects of Overe	exposure:	
Skin Contact:		exposure may cause skin Skin sensitization or allergic me individuals.	
Eyes:	Contact may cause irrublurred vision.	itation, redness, tearing and	
Inhalation :	No known health information on inhalation of vapors.		
Ingestion:	Low oral toxicity. LD (50) CAS 9003-36-5 LD (50) CAS 17557-23-2		
Chronic:	None known.	-	

8: FIRST AID:

Inhalation	Remove victim from exposure. If difficulty with breathing; administer oxygen and seek immediate medical assistance.
Eyes:	Flush with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
Skin:	Wash with soap and water; get medical attention if irritation persists.
Ingestion:	Do not give liquid if victim is unconscious or very drowsy; otherwise give no more than two glasses of water or milk and induce vomiting with two tablespoons of Syrup of Ipecac or by touching finger to back of victim's throat. Keep victim's head below hips while vomiting. Seek medical attention.

9. SPECIAL PROTECTION INFORMATION:

HMIS Pers	onal Protection C (Saftey Glasses, Gloves, Apron)		
Ventilation:	Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to prevent build-up of heavy vapors.		
Personal	Use eye protection. Selection of specific items such as		
Protection:	gloves, boots and apron will depend on the operation.		

10. ADDITIONAL INFORMATION:

IV. ADDITION	AL IIII ORIIIATION.
DOT Proper Shipping Name:	Epoxy resin mixture, not regulated
DOT Hazard Class or Division:	Not regulated
Identification Number:	N/A
Packing Group:	N/A
Labels Required:	N/A
WHMIS Classification:	Class B, Div. 3; Class D, Div. 2, Sub. B.
WHMIS Labeling:	Stylized T
Storage Conditions:	Keep containers tightly sealed. Store in dry and cool areas. Avoid freezing conditions.
Shelf life:	18 months, minimum.
Special Instructions:	Storage recommendations: Store at room temperature. Do not allow to freeze.

The information given herein is given in good faith. No warranty, expressed or implied, is made regarding the accuracy of these data or the results obtained from the use thereof. All materials may present unknown health hazards and must be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Consult ChemCo Systems Inc. for further information.

MSDS 026A 02/15